

ALPHA *coustic* - TRAP

**Bass Traps Absorbers
BOX & SOLO TYPES**

SOUND ABSORPTION CO-EFFICIENT



Sound Absorption Co-efficient Curves
according to ISO 354.2008 measured in
the Acoustics Laboratory of the
National Technical University of Athens

Design and Production according to International Standard ISO 9001.2008.

Vers. 5-14

#	Order Code	Description	Sound Absorption Co-efficient α_n Graph (ISO 354)	Sound Absorption Co-efficient α_n Frequency Spectrum (Hz)						
				F (Hz)						
1	B120B25	TRAP 120x60x30cm Box Type with membrane		F (Hz)	63	80	100	125	160	200
				α_n	0.13	0.31	0.83	0.76	0.63	0.43
				F (Hz)	250	315	400	500	630	800
				α_n	0.30	0.31	0.31	0.24	0.23	0.18
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.16	0.16	0.22	0.13	0.15	0.12				
2	B120B25W30	TRAP 120x60x25cm Box Type with two types of membrane		F (Hz)	63	80	100	125	160	200
				α_n	0.19	0.35	0.87	0.68	0.86	0.58
				F (Hz)	250	315	400	500	630	800
				α_n	0.52	0.44	0.34	0.32	0.27	0.23
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.23	0.16	0.24	0.17	0.17	0.22				
3	B120M8	TRAP 120x60x25cm Box Type with membrane		F (Hz)	63	80	100	125	160	200
				α_n	0.21	0.25	0.75	0.44	0.57	0.38
				F (Hz)	250	315	400	500	630	800
				α_n	0.29	0.30	0.27	0.24	0.20	0.16
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.16	0.14	0.19	0.14	0.15	0.20				
4	B120M12	TRAP 120x60x25cm Box Type with membrane		F (Hz)	63	80	100	125	160	200
				α_n	0.14	0.44	1.14	0.82	0.76	0.48
				F (Hz)	250	315	400	500	630	800
				α_n	0.36	0.37	0.31	0.32	0.28	0.21
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.22	0.21	0.30	0.15	0.22	0.16				

#	Order Code	Description	Sound Absorption Co-efficient α_n Graph (ISO 354)	Sound Absorption Co-efficient α_n Frequency Spectrum (Hz)						
				F (Hz)						
5	B120W190	TRAP 120x60x25cm Box Type with membrane		F (Hz)	63	80	100	125	160	200
				α_n	0.17	0.36	1.05	0.52	0.66	0.54
				F (Hz)	250	315	400	500	630	800
				α_n	0.37	0.38	0.42	0.47	0.36	0.25
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.43	0.22	0.23	0.20	0.17	0.14				
6	B120W80	TRAP 120x60x25cm Box Type with membrane		F (Hz)	63	80	100	125	160	200
				α_n	0.19	0.30	0.56	0.24	0.33	0.29
				F (Hz)	250	315	400	500	630	800
				α_n	0.29	0.28	0.22	0.19	0.24	0.15
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.15	0.13	0.19	0.12	0.13	0.14				
7	B120W30	TRAP 120x60x25cm Box Type with membrane		F (Hz)	63	80	100	125	160	200
				α_n	0.14	0.48	0.71	0.63	0.65	0.43
				F (Hz)	250	315	400	500	630	800
				α_n	0.38	0.32	0.27	0.27	0.21	0.20
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.20	0.16	0.18	0.14	0.18	0.17				
8	B120F+R	TRAP 120x60x25cm Box Type without membrane, with special textile & fiber sound absorption slab		F (Hz)	63	80	100	125	160	200
				α_n	0.14	0.16	0.53	0.73	0.92	1.10
				F (Hz)	250	315	400	500	630	800
				α_n	0.93	0.95	0.89	0.91	0.89	0.85
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.77	0.78	0.77	0.52	0.59	0.65				

#	Order Code	Description	Sound Absorption Co-efficient α_n Graph (ISO 354)	Sound Absorption Co-efficient α_n Frequency Spectrum (Hz)						
				F (Hz)						
9	B120B+R	TRAP 120x60x25cm Box Type with membrane, with additional fiber sound absorption slab		F (Hz)	63	80	100	125	160	200
				α_n	0.26	0.67	0.72	0.47	0.61	0.48
				F (Hz)	250	315	400	500	630	800
				α_n	0.55	0.75	0.92	0.88	0.95	0.90
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.86	0.76	0.78	0.71	0.72	0.78				
10	B120M8+R	TRAP 120x60x25cm Box Type with membrane, with additional fiber sound absorption slab		F (Hz)	63	80	100	125	160	200
				α_n	0.27	0.50	0.63	0.42	0.67	0.49
				F (Hz)	250	315	400	500	630	800
				α_n	0.57	0.72	0.86	0.99	0.97	0.87
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.85	0.75	0.81	0.74	0.78	0.76				

#	Order Code	Description	Sound Absorption Co-efficient α_n Graph (ISO 354)	Sound Absorption Co-efficient α_n Frequency Spectrum (Hz)						
				F (Hz)						
1	S120B+R	TRAP-SOLO 120x60x5cm Frame Type with membrane and fiber sound absorption slab behind		F (Hz)	63	80	100	125	160	200
				α_n	0.11	0.21	0.38	0.60	0.55	0.47
				F (Hz)	250	315	400	500	630	800
				α_n	0.42	0.46	0.52	0.41	0.29	0.26
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.28	0.16	0.23	0.20	0.14	0.12				
2	S120M20+R	TRAP-SOLO 120x60x5cm Frame Type with membrane with additional outer fiber sound absorption slab		F (Hz)	63	80	100	125	160	200
				α_n	0.05	0.17	0.19	0.52	0.44	0.40
				F (Hz)	250	315	400	500	630	800
				α_n	0.51	0.53	0.76	0.80	0.88	0.81
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.80	0.68	0.72	0.69	0.78	0.67				
3	S120F+R	TRAP-SOLO 120x60x5cm Frame Type with special textile without membrane and with additional fiber sound absorption slab		F (Hz)	63	80	100	125	160	200
				α_n	0.12	0.16	0.29	0.81	0.91	0.92
				F (Hz)	250	315	400	500	630	800
				α_n	0.90	0.92	0.84	0.82	0.90	0.84
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.90	0.84	0.77	0.68	0.89	0.71				
4	S120FB+R	TRAP-SOLO 120x60x5cm Frame Type with special textile with membrane and fiber sound absorption slab in between		F (Hz)	63	80	100	125	160	200
				α_n	0.17	0.18	0.59	0.79	0.66	0.63
				F (Hz)	250	315	400	500	630	800
				α_n	0.54	0.51	0.59	0.42	0.41	0.37
				F (Hz)	1000	1600	2000	3150	4000	5000
α_n	0.35	0.41	0.37	0.28	0.17	0.22				