

SOUND INSULATION PUR GEDICOUSTIC

Product data:

Item n°:	4195
EAN-Code:	4007155124717
Size:	5 m x 0,5 m x 6 mm (2,5 m ² /Roll)
box content:	10 Rolls/Pack



Use and advantages:

Sound absorbing PUR foam with special coating, suitable as base for application of tapestry or wallpaper - no Vinyl wallpaper!

- easy to process
- protection against humidity
- thermal insulation
- special texture

Tecnical data:

Material:	Polyurethane (PUR)
Thickness:	6 mm
Tensile Strength (RR):	> 900 kPa according to ISO 1798
Ultimate Elongation (ER):	10% according to ISO 1798
Tear Resistance (TR):	> 10 N/cm according to ISO 8067
Thermal conductivity:	0,13 m ² .°K/W according to NF T 56-124
Sound absorption:	0,25 α_w according to ISO 11654 (24% for 1000 Hz, 62% for 2000 Hz, 89% for 3000 Hz)

Processing:

The underground has to be absorbent, clean and free of dust and grease.
Prime with Phonicolle before processing. Apply glue with a fine notched trowel. Place Gedicoustic with the flocked foam side towards the wall and press it carefully. Drying time is 2 to 5 days. For successive wallpapering: for supporting the sound insulation effect ideally put some light tapestry using a standard wallpaper glue. **Attention: do not apply Vinyl wallpaper!** In order to preserve the sound-absorbing effect of Gedicoustic, we recommend a wallpaper with fissile peelable wallpaper. Later coat of paint: in order to avoid damage to Gedicoustic, we recommend the bonding of a recoatable special film. Only paint with acrylic paint!